

Secvest Wireless Key Switch

Art. no. FUBE50060

Page 1 of 2



- Easy installation and operation
- Sturdy housing
- Cylinder guard

The Secvest 2WAY wireless key switch is an optional module for the Secvest 2WAY. It allows you to conveniently arm and disarm your alarm system simply by turning a key. Due to the modern design, the wireless key switch can be integrated perfectly into any entrance area. No more forgetting your code with the wireless key switch: This component of the Secvest family replaces entering a code at the alarm panel or at the control unit by the simple turn of a key. Two integrated LED display the status of the system. This avoids false alarms caused by wrong operation. Communication between the center and its components takes place on 868.6625 MHz - a radio frequency which is exclusively reserved for security purposes. The latest FM radio technology with millions of codes and duplex antenna technology guarantees reliable transmission of the signals. Protection class IP55 lets you also use the wireless key switch in protected outdoor areas.

Secvest Wireless Key Switch

Art. no. FUBE50060

Page 2 of 2

Technical Data:

Dimensions	(WxHxD) 87x117x47 mm
Battery type	3.6 V AA Li battery (FU2992) or 12 V DC
Width	87 mm
Radio frequency	868,6625 MHz
Transmission power	10
Housing material	Aluminium and plastic
Height	117 mm
Length	47 mm
Max. battery life	2 year(s)
Max. operating temperature	55 °C
Max. receiving range (outdoors)	100 m
Max. receiving range (building)	30 m
Max. sending range (outdoors)	100 m

Max. sending range (building)	30 m
Min. operating temperature	-10 °C
Installation location	Indoors and protected outdoor areas
Net weight	0.55 kg
Tamper monitoring	Yes
IP protection class	55
Voltage monitoring	Yes
DC voltage supply	3,6/12 V
Status display	Yes
Power consumption	36 mA
Environmental class	II