

Day/Night PTZ 720p Network dome camera

Art. no. TVIP81000

Page 1 of 3



- Pan/tilt/zoom network camera (PTZ)
- 20x motorized zoom lens
- 8 tours with up to 32 preset positions per tour
- HD 720p resolution: 1280 x 720 @ 25 fps (H.264)
- Dual stream: Recording in HD, lower resolution for app access
- Good pictures in low light (3D DNR noise reduction)
- Control the direction of view via network and RS-485
- Privacy masking for hiding of third-party areas
- Watchman and alarm functions (7 alarm inputs and 2 alarm outputs)
- Protection class IP66 and integrated heating (outdoor dome only)

The PTZ network dome camera provides discreet, powerful surveillance. High-resolution images, control options, a high-quality zoom lens, and alarm functions ensure efficient monitoring. The moving 24-hour watchman sets standards: Easily integrated into existing IP networks, it combines the optical precision of a Speed Dome camera with the flexibility and readiness for the future of a network camera.

PTZ function: Pan, tilt, zoom

The 20x autofocus motorized zoom allows you to monitor the desired image section even across great distances. In conjunction with the HD resolution and pan/tilt technology, a PTZ IP camera monitors a large area: The movement can be automated – and every tour can manage up to 32 preset positions. The view direction can also be controlled manually via the network from a PC or control panel with an RS-485 connection. People and moving objects can be easily tracked in this way.

Clear images in HD720p, even in low light

With high resolution in HD720p (1280x720 pixels), the camera provides images that can be used. Even in low light: Thanks to sophisticated noise reduction (3D DNR), bothersome image noise is minimized – for clear images even when the lighting is weak, shadows are darkening the image, etc. In complete darkness, the camera works in light-sensitive black/white mode.

Day/Night PTZ 720p Network dome camera

Art. no. TVIP81000

Page 2 of 3

Suitable for indoor or outdoor use

The network camera is available as an indoor dome (TVIP81000) and outdoor dome (TVIP81100). The indoor dome can be screwed to the ceiling or integrated into suspended ceilings and is suitable for shops, offices, and warehouses, for example. With IP66 protection class and integrated heating, the outdoor dome withstands all weather – a weatherproof housing is not required.

Day/Night PTZ 720p Network dome camera

Art. no. TVIP81000

Page 3 of 3

Technical Data:

Dimensions	(HxØ) 243 x 183.4 mm
Alarm input (NO/NC)	7
Alarming	E-Mail / FTP / relay output
Number of streams	2
Number of tours	8
Audio	G.711ulaw/G.711alaw/G.726
Resolution modes	1280 x 720, 1280 x 960, 704 x 576, 352 x 288, 176 x 144 pixel
Motion detection	8 zones
Image sensor	1/3" Progressive Scan CMOS
Pixels (effective)	1280(H) x 720(V) pixel
Pixels (total)	1280(H) x 720(V) pixel
Frame rate	MJPEG: 704 x 576 @ 25 fps, MPEG-4: 1280 x 720 @ 25 fps, H.264: 1280 x 720 @ 25 fps
Width	220 mm
Focal length	4,3 – 86,0 mm
Electronic shutter	1 ~ 1/100000 seconds
Backlight compensation	Soft-WDR, BLC
Height	243 mm
Horizontal angle of view	3,2 – 54,1 °
Camera type	Network PTZ dome camera
Power consumption	40 W
Humidity	0 – 90
Max. resolution @ frame rate	1280 x 720 @ 25 fps
Max. operating temperature	50 °C
Max. humidity	90 %
Min. operating temperature	-10 °C

Minimum illumination (color)	0.05
Minimum illumination (B/W)	0.005
Video network bandwidth	32 kBit/s – 16 MBit/s
LAN network access	RJ45
Network camera protocols	IPv4/IPv6, HTTP, HTTPS, 802.1x, Qos, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, ICMP, DHCP, PPPoE
Lens	4,3 – 86,0 mm
Optical zoom	20x
Private zones	24
Protocols	Pelco-D, Pelco-P, self adaptive
Noise reduction	3D DNR
Relay output	2
Software	ABUS VMS, Internet Explorer 6, Safari, Mozilla Firefox
AC voltage supply	24 V
Power consumption	1500 mA
Day/night switching	IR cut can be swivelled electromagnetically
Encryption	HTTPS
Video compression	H.264, MPEG-4, MJPEG
White balance	Ja
Certifications	CE, RoHS, Reach